

Technical Data Sheet (Version 1. 2025)

SF U Bolt




PROPERTIES

- **Material:** Steel with min. tensile strength of 360 N/mm²
- **Zinc plating:** Electro zinc plated, $\geq 5 \mu\text{m}$
Also available with Rubber lining.

ADVANTAGES/BENEFITS

- Good for use as a guide mounting.
- The U-Bolt's two screws allow for ideal adaptation to suit the outer pipe diameter.

TECHNICAL DATA



Art.No.	U Bolt	Size	Threaded Dia	Width	Length	Length	Quantity Per Box
	Range				L1	L2	
	(mm)	(inch)	(mm)	(mm)	(mm)	(mm)	
SFUB26101	13-17	3/8"	6	24	35	18	100
SFUB26102	15-21	1/2"	6	28	40	22	100
SFUB26103	20-27	3/4"	6	36	50	30	100
SFUB26104	26-34	1"	8	43	55	30	100
SFUB26105	33-42	1-1/4"	8	51	68	35	100
SFUB26106	40-49	1-1/2"	8	58	70	35	100
SFUB26107	50-60	2"	8	69	80	35	50
SFUB26108	66-76	2-1/2"	10	88	110	38	50
SFUB26109	80-90	3"	10	102	115	45	50
SFUB26110	90-102	3-1/2"	10	116	145	50	50
SFUB26111	102-114	4"	12	128	156	55	25
SFUB26112	131-140	5"	12	156	185	65	25
SFUB26113	168	6"	12	184	210	65	25
SFUB26114	219	8"	12	236	270	65	25